



Environmental Product Declaration

ISKO™

for NZ-286986 and NZ-286497 denim garment in accordance with ISO 14025

Programme

The International EPD® System, www.environdec.com
EPD Turkey, www.epdturkey.org

Programme Operator

EPD International AB & EPD Turkey

Date of Publication (issue): 2021-04-13

Date of Validity: 2026-04-11

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com

EPD Registration Number: S-P-03502

Owner of the Declaration: ISKO™ ISKO Division, Sanko Tekstil İşletmeleri San. ve Tic. A.S. Organize Sanayi Bölgesi 3.Cadde 16400 İnegöl/Bursa/Turkey

Garment Manufacturer: Cross Textiles – Şık Makas Giyim Sanayi ve Ticaret A.Ş. 15 Temmuz Mah, 1507 Sok No:5 Bağcılar /İstanbul/TURKEY

Programme Operator	EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden E-mail: info@environdec.com Regional Office: EPD Turkey, Nef 09 B Blok 7/15 Kağıthane/ Istanbul, Turkey www.epdturkey.org
Product Category Rules (PCR)	Jackets, coats and other similar outdoor garments 2019:04, version 1.02 UN CPC 282 General Program Instructions 3.01
PCR Review Was Conducted By	The Technical Committee of the International EPD® System. A full list of members available on www.environdec.com. Chair of the PCR review: Hüdai Kara Contact via: info@environdec.com
Verification	Independent verification of the declaration and data, according to ISO 14025:2006: <input type="checkbox"/> EPD process certification <input checked="" type="checkbox"/> EPD verification
Third Party Verifier	Vladimír Kočí, PhD Šárecká 5, 16000 Prague 6, Czech Republic www.lcastudio.cz Approved by: The International EPD® System Technical Committee, supported by the Secretariat
Data Follow Up	Procedure for follow-up of data during EPD validity involves third party verifier: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
LCA Study & EPD Design Conducted By	Semtrio Sustainability Consulting BUDOTEK Teknopark, No 4/21, Umraniye / Istanbul Turkey www.semtrio.com

ISKO™ has the sole ownership, liability and responsibility of this EPD. For further information about this EPD or its content, please contact **Mrs. Ebru Ozkucuk Guler** at sustainability@isko.com.tr.

EPDs within the same product category but from different programmes may not be comparable.

OUR DENIM

“Denim fabrics look at people, and we explore our denim world through their lifestyles.”



ISKO™, the leading ingredient brand on a global level, is the first denim producer in the world to be recognized with the Nordic Swan and EU Ecolabel certifications. It has a production capacity of 300 million meters of fabric per year, with 2000 state-of-the-art automatic looms. It creates the soul of jeans, the essence of the most popular fashion style that has become universal.

ISKO™'s vision is as international as the love for denim. It can adapt to different contexts and markets, becoming a point of reference for the most famous designers and inspiring new fashion trends.

INNOVATION since 1904

With a global presence and offices in 35 countries, ISKO™ is part of SANKO TEKSTIL, the textile division of SANKO Group.

ISKO™'s route to textiles began in 1904 and in 1989 we opened our 300,000 m2 manufacturing plant, making ISKO™ the world's largest denim manufacturer under one roof.

ISKO Philosophy



PERFORMANCE

ISKO™ is the denim specialist, all fabrics are characterized by an advanced technology and the deeply-rooted care for quality, during all the integrated production from yarn to finishing processes.



INNOVATION

ISKO™'s mission is to always keep in touch with the latest trends and also to anticipate times. ISKO™'s research center is certified by the Turkish government and it consists of more than 25 textile engineers, specialists in creating new denim products.




SUSTAINABLE

Sustainability at ISKO™ we rethink our sourcing strategies and refuse to source more material than we need. Our waste management innovations reduce the environmental performance impact from yarn to fabric production, by using reused and recycled materials.

OUR COMMITMENT

Sustainability is inherent to ISKO's DNA: every day we value responsibility and a 360-degree innovation. This is something we take seriously, and we are dedicated to doing this with beauty, heart, and creativity.



CERTIFIED RECYCLED MATERIALS USAGE

At ISKO™ we blend certified recycled materials with the reused cotton. Producing recycled polyester uses less energy than making virgin polyester and lessens the dependence on petroleum as a raw material. Both factors reduce our overall carbon footprint.



CREATING REUSED COTTON FROM LOSS

When raw cotton is processed into yarn, 10% of it is typically expected to be lost as waste. At this stage ISKO™ differentiates itself as we continually trace, track, and monitor this loss and reuse the cotton by adding it back into the spinning process.

All our reused cotton is Content Claim Standard (CCS) certified.



Product NZ-286986

Content Declaration



Materials in the Product	% in the product	Material Composition
Denim Fabric	> 95%	%60CO %20RUC %20RCO
Lining	0%	%74RCY.PES %13RCY.CO %13ORG.CO
Fusing	< 1%	100% PES
Paper Labels	< 1%	100% Paper
Metal Accessories	> 1%	100% Metal

-Packaging: PE packaging film is used to cover the end products. Classified as Distribution Packaging: designed for the purposes of transport, handling and/or distribution.

-Chemicals used in ISKO™ and Cross Textiles manufacturing comply with the Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Technical Specifications*

Characteristics	Reference Standard	Units	Results
Constructive Characteristics			
Composition	Regulation EU No 1007/2001	%	60% CO 20% RUC 20% RCO
For woven materials: Weave	ISO 3572	-	3/1 RHT
Mass per unit area	(ASTM D3776)	g/m ²	355
Width	(ASTM D3774)	cm	160
Dyeing			
Colour Index	-	-	-
Performance Characteristics			
For woven materials: Abrasion strength (Martindale)	ISO 12947-2	grade	-
For woven materials: Tear strength	ASTM D1424	grade	Warp: 4750 gr Weft: 2400 gr
For woven materials: Tensile strength	ASTM D5034	grade	Warp: 75.9 kg Weft: 34 kg
pH of water extract	EN ISO 3071	grade	7.4
Colour Fastness			
Colour fastness to artificial light: Xenon arc fading lamp test	EN ISO 105 B02	grade	-
Acid and alkaline perspiration	EN ISO 105 E04	grade	-
Dry and wet rubbing	AATCC 8	grade	Dry: 4 - Wet: 1

Product NZ-286497

Content Declaration




Materials in the Product	% in the product	Material Composition
Denim Fabric	> 95%	%60CO %20RUC %20RCO
Lining	0%	-
Fusing	< 2%	100% PES
Paper Labels	< 1%	100% Paper
Metal Accessories	> 2%	100% Metal

-Packaging: PE packaging film is used to cover the end products. Classified as Distribution Packaging: designed for the purposes of transport, handling and/or distribution.

-Chemicals used in ISKO™ and Cross Textiles manufacturing comply with the Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Characteristics	Reference Standard	Units	Results
Constructive Characteristics			
Composition	Regulation EU No 1007/2001	%	60% CO 20% RUC 20% RCO
For woven materials: Weave	ISO 3572	-	3/1 RHT
Mass per unit area	(ASTM D3776)	g/m ²	360
Width	(ASTM D3774)	cm	160
Dyeing			
Colour Index	-	-	-
Performance Characteristics			
For woven materials: Abrasion strength (Martindale)	ISO 12947-2	grade	-
For woven materials: Tear strength	ASTM D1424	grade	Warp: 4927 gr Weft: 2590 gr
For woven materials: Tensile strength	ASTM D5034	grade	Warp: 74.8 kg Weft: 33.5 kg
pH of water extract	EN ISO 3071	grade	8.1
Colour Fastness			
Colour fastness to artificial light: Xenon arc fading lamp test	EN ISO 105 B02	grade	-
Acid and alkaline perspiration	EN ISO 105 E04	grade	-
Dry and wet rubbing	AATCC 8	grade	Dry: 4 - Wet: 2



Time representativeness: The production data in the LCA study represents the period from 1st January 2021 and 31st January 2021

Database and LCA software used: SimaPro v9.1 software with Ecoinvent v3.6 database

Excluded lifecycle stages: Retail, Customer Travel, Customer Use and End-of-life stages have been excluded in the system boundary and not taken into account in the LCA study.

Geographical scope of the EPD	Worldwide
Functional Unit	1 pair of jeans delivered to an average retailer platform
EPD Type (System Boundary)	Cradle-to-gate with options
Data Quality and Data Collection	Site specific data is collected for the core and upstream processes from Cross Textiles and ISKO™ for the period between 1 st January to 31 st January 2021. Samples are produced for both products. Specific energy and chemical consumption values are collected from the manufacturing per load per machine. Selected generic data is used for upstream processes and obtained from Ecoinvent v3.6. Specific and selected generic data achieve the ISO 14044 data quality requirements and time representatives. Denim fabric makes the main component of the jeans and impacts caused by denim fabric manufacturing is solely depending on the denim mill. Denim fabric data is collected from the denim mill per individual product.
Allocation	Allocation was avoided by dividing the unit process into two or more sub-processes and collecting the environmental data related to these sub-processes. There has been no allocation conducted for the LCA study.
Calculation Methods	All resource use values are calculated from Cumulative Energy Demand V1.11; net use of fresh water has been calculated from SimaPro Inventory result outputs. Potential environmental impacts are calculated with the CML-IA baseline V 3.06; ReCiPe 2016 Midpoint (H) v 1.04; Formation potential of tropospheric ozone (POCP) from LOTOS-EUROS as applied in ReCiPe Midpoint (H) v 1.13, 2008; IPCC 2013 GWP 100a V1.03 and USEtox 2 (recommended + interim) v.1.0 and Water Scarcity indicator from Pfister et al 2009 v1.02 methods in SimaPro software.
Cut-off Rules	Life Cycle Inventory data for a minimum of 99 % of total inflows to the three life cycle stages have been included. Waste generated from core presses have been excluded due to the cut-off rule. Impacts caused by treatment operations have been calculated lower than 1% environmental relevance. Regarding material and chemical inputs, no cut-off rule has been applied.

More information regarding to ISKO™ and its products is available on www.isko.com.tr.

Resource Use for NZ-286986

Resource Use							
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total	
Primary Energy Resources Renewable	Use as energy carrier	MJ, net calorific value	19.77	0.49	0.972	0.367	21.60
	Use as raw materials	MJ, net calorific value	0	0	0	0	0
	TOTAL	MJ, net calorific value	19.77	0.49	0.972	0.367	21.60
Primary Energy Resources Nonrenewable	Use as energy carrier	MJ, net calorific value	59.37	1.7	7.9	13.5	82.42
	Use as raw materials	MJ, net calorific value	0	0	0	0	0
	TOTAL	MJ, net calorific value	59.37	1.7	7.9	13.5	82.42
Secondary Material	kg	0.323	0	0	0	0.32	
Renewable Secondary Fuels	MJ, net calorific value	0	0	0	0	0	
Nonrenewable Secondary Fuels	MJ, net calorific value	0	0	0	0	0	
Net use of Fresh Water	m³	0.365	0.002	0.019	0.002	0.39	

Waste Production for NZ-286986

Waste Production						
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total
Hazardous Waste	kg	0.00049	INA	0.015	0	0.015
Non-hazardous Waste	kg	0.0036	INA	0.16	0	0.163
Radioactive Waste	kg	0	INA	INA	0	0

INA=Indicator Not Available

Potential Environmental Impacts for NZ-286986

Environmental Impacts							
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total	
Global Warming Potential (GWP100a)	Fossil	kg CO ₂ eq	4.05	0.11	0.449	0.84	5.45
	Biogenic	kg CO ₂ eq	0.1	0.024	0.006	0.011	0.14
	Land Use and Land Transformation	kg CO ₂ eq	0.25	0.001	1.32E-04	6.48E-04	0.25
	TOTAL	kg CO ₂ eq	4.4	0.136	0.455	0.854	5.84
Acidification Potential (AP)	kg SO ₂ eq	0.017	0.005	0.001	0.004	0.027	
Eutrophication Potential (EP)	kg PO ₄ ³⁻ -eq	0.012	1.34E-04	0.003	0.001	0.015	
Photochemical oxidant formation potential (POFP)	kg NMVOC eq	0.0116	0.001	0.001	0.005	0.019	
Abiotic Depletion Potential-Elements	kg Sb eq	3.68E-05	8.30E-06	8.30E-07	1.95E-05	6.55E-05	
Abiotic Depletion Potential-Fossil Fuels	MJ, net calorific value	52.85	1.4	6.7	12.0	73.01	
Water Scarcity Potential	m³ eq	15.65	0.1	0.984	0.062	16.79	

Output Flows for NZ-286986

Output Flows						
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total
Components For Reuse	kg	0	INA	0	0	0
Material For Recycling	kg	0.0181	INA	0.054	0	0.072
Materials For Energy Recovery	kg	0	INA	0	0	0
Exported energy, Electricity	MJ	0	INA	0	0	0
Exported energy, Thermal	MJ	0	INA	0	0	0

INA=Indicator Not Available

Resource Use for NZ-286497

RESOURCE USE							
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total	
Primary Energy Resources Renewable	Use as energy carrier	MJ, net calorific value	24.36	0.62	0.820	0.463	26.26
	Use as raw materials	MJ, net calorific value	0	0	0	0	0
	TOTAL	MJ, net calorific value	24.36	0.75	0.820	0.463	26.26
Primary Energy Resources Nonrenewable	Use as energy carrier	MJ, net calorific value	71.05	2.9	6.7	17.0	97.70
	Use as raw materials	MJ, net calorific value	0	0	0	0	0
	TOTAL	MJ, net calorific value	71.05	2.9	6.7	17.0	97.70
Secondary Material	kg	0.399	0	0	0	0.40	
Renewable Secondary Fuels	MJ, net calorific value	0	0	0	0	0	
Nonrenewable Secondary Fuels	MJ, net calorific value	0	0	0	0	0	
Net use of Fresh Water	m ³	0.449	0.003	0.020	0.003	0.47	

Waste Production for NZ-286497

Waste Production						
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total
Hazardous Waste	kg	0.00061	INA	0.018	0	0.019
Non-hazardous Waste	kg	0.00449	INA	0.22	0	0.222
Radioactive Waste	kg	0	0	INA	0	0

INA=Indicator Not Available

Potential Environmental Impacts for NZ-286497

Environmental Impacts							
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total	
Global Warming Potential (GWP100a)	Fossil	kg CO ₂ eq	4.924	0.18	0.386	1.06	6.55
	Biogenic	kg CO ₂ eq	0.120	0.025	0.006	0.014	0.16
	Land Use and Land Transformation	kg CO ₂ eq	0.308	0.001	1.38E-04	8.17E-04	0.31
	TOTAL	kg CO ₂ eq	5.352	0.206	0.392	1.077	7.03
Acidification Potential (AP)	kg SO ₂ eq	0.020	0.011	0.001	0.005	0.04	
Eutrophication Potential (EP)	kg PO ₄ ³⁻ eq	0.015	2.11E-04	0.003	0.001	0.02	
Photochemical oxidant formation potential (POFP)	kg NMVOC eq	0.014	0.002	0.001	0.007	0.02	
Abiotic Depletion Potential-Elements	kg Sb eq	4.4E-05	1.15E-05	7.90E-07	2.46E-05	8.10E-05	
Abiotic Depletion Potential-Fossil Fuels	MJ, net calorific value	63.28	2.5	5.7	15.1	86.59	
Water Scarcity Potential	m ³ eq	19.27	0.1	1.066	0.079	20.50	

Output Flows for NZ-286497

Output Flows						
Parameter	Unit	Upstream-Denim Fabric	Upstream-Garment Maker	Core	Downstream	Total
Components For Reuse	kg	0	INA	0	0	0
Material For Recycling	kg	0.0224	INA	0.068	0	0.091
Materials For Energy Recovery	kg	0	INA	0	0	0
Exported energy, Electricity	MJ	0	INA	0	0	0
Exported energy, Thermal	MJ	0	INA	0	0	0

INA=Indicator Not Available

ISO 14040: 2006 Environmental management | Life cycle assessment | Principles and framework

ISO 14044: 2006 Environmental management | Life cycle assessment | Requirements and guidelines

ISO 14025: 2006 Environmental labels and declarations | Type III environmental declarations | Principles and procedures

ISO 14020:2000 Environmental labels and declarations – General principles

The International EPD® System | www.environdec.com

The International EPD® System | The General Programme Instructions
<http://www.environdec.com/tr/The-International-EPD-System/General-Programme-Instructions/>

The International EPD® System | Jackets, coats and other similar outdoor garments 2019:04, version 1.02 UN CPC 282

Ecoinvent 3.6 database | <http://www.ecoinvent.org>

SimaPro LCA Software | <https://simapro.com>

ISKO™ | <http://www.isko.com.tr>

GaBi database | Cotton fiber (organic) (at gin gate) <http://www.gabi-software.com/in>

Van der Velden, N.M., Patel, M.T., Vogtlander, J.G., 2014 / LCA benchmarking study on textiles made of cotton, polyester, nylon, acryl, or elastane. | International Journal of Life Cycle Assessment 19, 331 - 356.

Environmental Improvement Potential of textiles (IMPRO Textiles) | <https://publications.europa.eu/en/publication-detail/-/publication/f8d0def8-4fd5-4d84-a308-1dfa5cf2e823/language-en>

Third Party Verifier

Vladimír Kočí, PhD

Šárecká 5, 16000 Prague 6,

Czech Republic

www.lcastudio.cz

Accredited or approved by: The International EPD® System



Owner of the Declaration

ISKO Division

Sanko Tekstil Isletmeleri San. ve Tic. A.S. Organize Sanayi Bölgesi 3.Cadde

16400 Inegol, Bursa | Turkey

www.iskodenim.com



LCA Author & EPD Design

Semtrio Sustainability Consulting

BUDOTEK Teknopark, No 4/21 Umraniye

Istanbul | Turkey

www.semtrio.com



More information about ISKO™'s approach to sustainability and its corporate social responsibility initiatives available via the CSR Team at sustainability@isko.com.tr

ISKO™

HEAD OFFICE

ISKO Division

Sanko Tekstil İşletmeleri San. ve Tic. A.S. Organize Sanayi
Bölgesi 3.Cadde 16400 Inegol / Bursa / Turkey

T: +90 224 280 77 00

F: +90 224 714 80 19

E: sustainability@isko.com.tr

E: eozkucuk@isko.com.tr

